

**5502UG Non-Paired - Residential, Light Commercial and Institutional Applications**

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

**Description:**

22 AWG stranded (7x30) bare copper conductors, polypropylene insulation, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Conductors	4
Total Number of Conductors	4
AWG	22
Stranding	7x30
Conductor Material	BC - Bare Copper

**INSULATION:**

Insulation Material	PP - Polypropylene
Nom. Insulation Wall Thickness	.006 in.

**OVERALL CABLING:**

Overall Cabling Color Code Chart	Black, Red, White, Green
----------------------------------	--------------------------

**OUTER SHIELD:**

Outer Shield Material	Unshielded
-----------------------	------------

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.015 in.

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.131 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	13 lbs/1000 ft.
Max. Recommended Pulling Tension	36.4 lbs.
Min. Bend Radius (Install)	1.3 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

## 5502UG Non-Paired - Residential, Light Commercial and Institutional Applications

NEC/(UL) Specification	CM
NEC Articles	800
CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

### FLAME TEST:

UL Flame Test	UL1685 UL Loading
CSA Flame Test	FT1

### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

### ELECTRICAL CHARACTERISTICS:

Nom. Capacitance Conductor to Conductor @ 1 KHz	20 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	16.2 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	2.2 Amps per conductor @ 25°C

### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
5502UG 001C1000	4 #22 PP FRPVC	C1000	13	BROWN	
5502UG 001C500	4 #22 PP FRPVC	C500	6.5	BROWN	
5502UG 001U1000	4 #22 PP FRPVC	U1000	14	BROWN	
5502UG 003C1000	4 #22 PP FRPVC	C1000	13	ORANGE	
5502UG 003C500	4 #22 PP FRPVC	C500	6.5	ORANGE	
5502UG 003U1000	4 #22 PP FRPVC	U1000	14	ORANGE	
5502UG 004C1000	4 #22 PP FRPVC	C1000	13	YELLOW	
5502UG 004C500	4 #22 PP FRPVC	C500	6.5	YELLOW	
5502UG 004U1000	4 #22 PP FRPVC	U1000	14	YELLOW	
5502UG 005C1000	4 #22 PP FRPVC	C1000	13	GREEN, DARK	
5502UG 005C500	4 #22 PP FRPVC	C500	6.5	GREEN, DARK	
5502UG 006C1000	4 #22 PP FRPVC	C1000	13	BLUE, LIGHT	
5502UG 006C500	4 #22 PP FRPVC	C500	6.5	BLUE, LIGHT	

**5502UG Non-Paired - Residential, Light Commercial and Institutional Applications**

5502UG 006U1000	4 #22 PP FRPVC	U1000	14	BLUE, LIGHT	
5502UG 007C1000	4 #22 PP FRPVC	C1000	13	VIOLET	
5502UG 007C500	4 #22 PP FRPVC	C500	6.5	VIOLET	
5502UG 007U1000	4 #22 PP FRPVC	U1000	14	VIOLET	
5502UG 008C1000	4 #22 PP FRPVC	C1000	13	GRAY	
5502UG 008C500	4 #22 PP FRPVC	C500	6.5	GRAY	
5502UG 009C1000	4 #22 PP FRPVC	C1000	13	WHITE	
5502UG 009C500	4 #22 PP FRPVC	C500	6.5	WHITE	
5502UG U4FC1000	4 #22 PP FRPVC	C1000	13	BEIGE U4F	
5502UG U4FC500	4 #22 PP FRPVC	C500	6.5	BEIGE U4F	
5502UG U4FU1000	4 #22 PP FRPVC	U1000	14	BEIGE U4F	
5502UG 008U1000	4 #22 PP FRPVC	U1000	14	GRAY	
5502UG 008U500	4 #22 PP FRPVC	U500	7.5	GRAY	
5502UG 009U1000	4 #22 PP FRPVC	U1000	14	WHITE	

Revision Number: 1      Revision Date: 08-26-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.