

Technical Data Sheet

RG6/U CCTV Coaxial Cable



2833 West Chestnut Street
 Washington, PA 15301
 Toll Free: (800) 245-4964
 Fax: (724) 222-6420
 www.westpenn-wpw.com

PART NUMBER:	806
DESCRIPTION:	RG6/U 18 Awg. Solid Bare Copper, 95% Bare Copper Braid and PVC jacket
NEC RATING:	CM
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor for: Security Cable- CCTV

Construction Parameters:

Conductor	18AWG Bare Copper
Stranding	Solid
Insulation Material	Gas injected Polyethylene
Insulation Thickness	.180" Nom.
Shield	95% Bare Copper Braid
Jacket Material	PVC
Overall Cable Diameter	0.270" Nom.
Approximate Cable Weight	36 Lbs/1M' Nom.
Flame Rating	UL1685

Electrical & Environmental Properties:

Temperature Rating	-20°C To +60°C
Operating Voltage	300 VRMS
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.
Nom. Velocity of Propogation	82%
Nom. Impedance	75 Ohms
DC Resistance per Conductor @ 20deg C	6.5 Ohms/1M' Nom.
Jacket Color	Black
RoHS Compliant	--

Nom. Attenuation

MHz	dB/100ft
1	.24
10	.52
50	1.18
100	1.83
400	3.95
700	5.38
1000	6.45

Mechanical Properties:

Max. Recommended Pull Tension	69 lbs
Min. Bend Radius (Install)	2.70"

Connectors:

75 Ohm 3pc. BNC	CN-BN73-5	(Crimp Tool): TL-107	(Stripping Tool): TL-121
Compression BNC Type	CN-BNCSNS-5	(Crimp Tool): TL-SNSA	(Stripping Tool): TL-SNSST
Compression RCA Type	CN-CSRCA-6	(Crimp Tool): TL-SNSA	(Stripping Tool): TL-CSST

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.
 The Jacket is sequentially footmarked.
 The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.